

# VScan-P

Live Scanner / Palm Scanner



## Features



**Palm Scanner**  
 · Four finger slaps, single rolls, single flat,  
 on thumb, half palm, writer's palm



**USB Interface Support**  
 · Compatible interface with USB 2.0



**FBI Certification**  
 · FBI IQS Appendix-F Certification



**SDK** Demo Program and SDK

## Specification

|                                |  |                              |                           |
|--------------------------------|--|------------------------------|---------------------------|
| <b>Fingerprint Type</b>        | Single finger Flat / Single Roll, Dual finger flat,<br>Four finger slap, Palm, Writer's palm | <b>Operating Temperature</b> | 0°C - 40°C                |
| <b>Resolution</b>              | 500 or 508dpi / 256 gray   | <b>Operating Humidity</b>    | 10 - 90%, non-condensing  |
| <b>Speed</b>                   | 20 frames per second (fps)   | <b>Operating Voltage</b>     | 12 VDC                    |
| <b>Platen Size</b>             | 155.9 X 144.8 mm   | <b>Dimension</b>             | 47.2 x 34.4 x 81 mm       |
| <b>Sensing Area</b>            | 130 X 130 mm(5.12" x 5.12")  | <b>Certification</b>         | CE                        |
| <b>Image Quality Standards</b> | FBI IQS Appendix F   | <b>Dust Water Resistance</b> | IP43                      |
| <b>Image format</b>            | raw, WSQ   | <b>Interface</b>             | USB 2.0 high speed (data) |
| <b>Weight</b>                  | 8.5Kg (Scanner only)   | <b>Operating System</b>      | Microsoft Windows         |

